

### Product designation

**BB 200/SL3 Electronic battery ballast unit 200 Watt** Article no. 742-0195

### Product description

The extremely compact electronic ballast unit BB 200/SL3 can be operated on battery with 22 - 34 volt and is steplessly dimmable (60 - 100 %). The electronic temperature and voltage management assures safe and reliable operation even at high ambient temperatures and with various battery voltages. The unit can be easily and securely coupled to the battery and charger by means of the SlideLock system (SL3).

### Scope of delivery

Electronic ballast unit with SlideLock system SL3

### Technical data

<b>Electronic ballast unit</b>	<b>BB 200/SL3</b>
Power output	200 W
Voltage	22-34 V DC
Power input	215 VA
Power variation (dimming)	100 % - 60 %
Protection class	II
IP protection	20
Battery connection	SlideLock system
Dimensions L x W x H	65 x 105 x 165 (mm) 2.6 x 4.1 x 6.5 (inch)
Weight	0.8 kg / 1.76 lb

Subject to change in the interest of product enhancement.

### Application

The compact dimensions and light weight make this ballast unit an ideal power-package for mains independent, mobile application, especially if the lighting equipment has to be carried on occasion. Due to the high operational reliability, the ballast unit is the optimum solution for all ENG and "on location" applications.