

### Product designation

**Electronic ballast unit EB 4 x 35 / 55 (230 V)**

Article no. 742-0220-X

**Electronic ballast unit EB 4 x 35 / 55 (120 V)**

Article no. 742-0120-X

### Product description

The compact electronic ballast unit EB 4 x 35 / 55 is switchable from 35 W to 55 W and suitable for use with Lumax fluorescent lights SB 14 and SB 24. With this ballast unit you have the option to operate four 35 W or four 55 W tubes. Using the incorporated controller you can regulate the power from 100-30 %, without displacement of colour, steplessly and linearly. A safety switch assures that the lamp connector remains voltageless till the lamp is plugged-in. The lamps can be switched on and off also when in operation (hot pluggable).

### Scope of delivery

Electronic ballast unit and mains cable

### Technical data

<b>Electronic ballast unit</b>	<b>EB 4 x 35 / 55 (230 V)</b>	<b>EB 4 x 35 / 55 (120 V)</b>
Power output	35 W / 55 W	35 W / 55 W
Voltage	200-240 V AC	100-120 V AC
Power variation (dimming)	100 % - 30 %	100 % - 30 %
Power requirement	switchable 260 VA	switchable 300 VA
Safety class	I	I
Dimensions L x W x H	503 x 132 x 62 mm 19.8 x 5.2 x 2.5 inch	503 x 132 x 62 mm 19.8 x 5.2 x 2.5 inch
Weight	1,8 kg 3.96 lb	1.9 kg 4.2 lb

Subject to change in the interest of product enhancement.

### Application

Due to the high operational reliability, the electronic ballast unit is ideal for rental and for applications "on location" for TV, broadcast, production and film.