

Product designation

Lumax SB 12
Lumax SB 14
Lumax SB 22
Lumax SB 24

Article no. 381-1012
Article no. 381-1014
Article no. 381-1022
Article no. 381-1024

Product description

The **kobold** Lumax fluorescent light banks convince with their solid design, compact dimensions, light weight and maximum reliability. The integrated barn doors are equipped with a maintenance-free unique hinge mechanism and are easy to position. The housings are rigid and feature strong plastic end-pieces, therefore ideal for horizontal operation while suspended.

Scope of delivery

Matching Lumax fluorescent tubes with 2 barn doors, operating instructions, carton packaging.

Technical data

Light banks	SB 12	SB 14	SB 22	SB 24
No. of tubes	2	4	2	4
Photometric at 2 m (6.5 ft) distance	150 lx	300 lx	350 lx	700 lx
Dimensions L x W x H (mm) (inch)	700 x 193 x 87 27.8 x 7.6 x 3.4	700 x 321 x 87 27.8 x 12.6 x 3.4	1310 x 193 x 87 51.6 x 7.6 x 3.4	1310 x 321 x 87 51.6 x 12.6 x 3.4
Weight with barn door, tubes and adapter plate (kg) (lb)	3.3 7.3	4.6 10.2	4.2 9.3	5.5 12.2
Length of lamp cable (m) (ft)	0.2 0.7	0.2 0.7	0.2 0.7	0.2 0.7

Application range

Lumax fluorescent light banks are lightweight, robust, simple to assemble and disassemble and easy to transport. Due to the rigid housing the light banks are ideal for ceiling mounting. The Lumax ballast units are dimmable. These features make the fluorescent light banks optimum for "on location" applications.

Accessories

fluorescent tube 20 W 5800 K with safety sheath	683-1075
fluorescent tube 20 W 5800 K with safety sheath without magenta filter	683-1076
fluorescent tube 40 W 5800 K with safety sheath	683-1136
fluorescent tube HO 55 W 5500 K with safety sheath	683-1138
fluorescent tube 20 W 3400 K with safety sheath	673-1075
fluorescent tube 20 W 3400 K with safety sheath without magenta filter	673-1076
fluorescent tube 40 W 3400 K with safety sheath	673-1136
fluorescent tube HO 55 W 3200 K with safety sheath	673-1138
T-support to accept two light banks	857-0100
adapter plate with ball joint with mount Ø 16 mm (5/8")	817-0810
double spigot Ø 16 mm (5/8")	MA 013
lamp cable, 3 m (10 ft) for SB 12/22	742-0719
lamp cable, 3 m (10 ft) for SB 14/24	742-0715
mains cable for ballast unit Lumax with Europe plug	742-0711
mains cable for ballast unit Lumax with USA plug	742-0712
mains cable for ballast unit Lumax with Swiss plug	742-0713
mains cable for ballast unit Lumax without plug	742-0714
light grid, parabolic, silver, for SB 12	033-0103
light grid, parabolic, silver, for SB 14	033-0102
light grid, parabolic, silver, for SB 22	033-0104
light grid, parabolic, silver, for SB 24	033-0101
light grid, black, for SB 12	033-0117
light grid, black, for SB 14	033-0114
light grid, black, for SB 22	033-0118
light grid, black, for SB 24	033-0116
transport bag for 1 x SB 24 or 2 x SB 14 systems, empty	733-0310
alu stand, 103-290 cm (3.4 - 9.5 ft), with spigot Ø 16 mm (5/8")	MA 005
alu stand, 88-250 cm (2.8 - 8.2 ft), with spigot Ø 16 mm (5/8")	MA 052